



**Cummins engine power**  
**Working spacing**  
**Pure working efficiency**

350 hp (268 kW)  
≥1,400 mm  
≥50 t/h

# **S935**

# **SUGARCANE**

# **HARVESTER**

# S935 SPECIFICATIONS >>>

## POWER SYSTEM

Cummins engine power	268 kW (Cummins)
Maximum speed	2,100 rpm
Emission	T3
Fuel tank capacity	530 L
Cylinder displacement	10.8 L

## DRIVING SYSTEM

Drive mode	Rear wheel hydraulic drive
Traveling mode	Wheeled
Steering mode	Front wheel steering

## TOPPER

Topper type	Standard topper and optional shredder topper
Lifting range of the topper	1,000-3,900 mm
Number of standard topper knives	6
Number of shredder topper knives	60

## PRIMARY EXTRACTOR

Number of blades	4
Fan RPM	1,200

## CROP DIVIDERS

Distance between the left and right crop dividers toes	1,500 mm
--	----------

## ELEVATOR

Conveying chain drive/rotation	Hydraulic/ Reverse rotation
Chain speed	Constant
Swing angle left and right	170°

## WHOLE VEHICLE

Maximum traveling speed	16 km/h
Maximum harvesting traveling speed	8 km/h
Weight	16,580 kg
Working spacing	≥1,400 mm
Pure working efficiency	≥50 t/h
Fire Extinguishing Device	Manual fire extinguisher 2-4KG

## PASSAGE

Passage width	Front 1100 Rear 900 mm
Feeder port	1,060 mm
Base cutter angle	18°/15° optional
Adjustable height of base cutter	0—270 mm
Number of knives per disk	10
Angle adjustment of the first knock-down roller	Manual mechanical adjustment
Number of rollers in the passage	13
Number of knives per drum	6 pcs / 8 pcs optional
Billet length	200--280 mm

